



Circuit Diagram

| PART NO. | L | Operating force |
|-------------|---|-----------------|
| MS-23D20-G2 | 2 | 250±100gf |
| MS-23D20-G3 | 3 | |
| MS-23D20-G4 | 4 | |

| ITEM | PART NAME | QTY. | MATERIAL | FINISHING |
|------|----------------|------|------------------|-----------|
| ⑤ | Contact Spring | 2 | Beryllium copper | Ag Plated |
| ④ | Terminal | 8 | Brass Strip | Ag Plated |
| ③ | Base | 1 | NYLON | Black |
| ② | Cover | 1 | SUS | Natural |
| ① | KNOB | 1 | NYLON | White |

| APPROVALS | | DATE |
|-----------|----------|-----------|
| DRAWN | G.M.Chen | 2014/8/18 |
| CHECKED | | |
| APPROVALS | | |

DERION 德芝隆
ELECTRONICS CO.,LTD

| | |
|-------------|----------------|
| TITLE: | SLIDE SWITCHES |
| PART NO. | MS-23D20-G |
| UNIT: mm | SCALE: 1:1 |
| DRAWING NO. | SHEET 1 OF 1 |

| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|---------|------|-------|--------------|---------|--------|--------|
| | A | | NEW | | | |

| | | | | | |
|----------------|-------------|-------------|------------|-----------|-----------|
| TOLERANCES ARE | 30~以上 ±0.30 | 10~30 ±0.20 | 5~10 ±0.15 | ~ 5 ±0.10 | ANGLE ±2° |
|----------------|-------------|-------------|------------|-----------|-----------|