


NOTE:
 Operating Force:
 lever portion 70 ± 40 gf
 Push portion 200 ± 40 gf
 Travel: -25° 0° +25° Pushportion 0.9±0.1mm

		0° (Hatched=NO)			
TER	ANG.	(25°)	(18°)	(18°)	(25°)
①		Hatched			
②				Hatched	
③		Hatched	Hatched	Hatched	Hatched

CCW ← → CW

CODE TABLE



ITEM	PART NAME	QTY.	MATERIAL	FINISHING
⑥	Contact	1	F.Ag/Brass	Plating silver
⑤	Terminal	5	Brass(0.15t)	Plating silver
④	Base	1	LCP	Black
③	Spring	1	SUS	Natural
②	Cover	1	SUS	Natural
①	Keystoke	1	PA46	Black

APPROVALS		DATE	DERON 德之隆® ELECTRONICS CO.,LTD	
DRAWN	G.M.Chen	2015/3/30	TITLE:	MULTIFUNCTIONAL SWITCHES
CHECKED			PART NO.	BLQ-1531-01
APPROVALS			UNIT: mm	SCALE: 1:1
TOLERANCES ARE	30~BLK ±0.30	ANGLE	DRAWING NO.	SHEET 1 OF 1
	10~30 ±0.20	±2°		
	5~10 ±0.15			
	~ 5 ±0.10			

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			