

PCB Layout recommended


PART NO.	
TD-1113SA	
TD-1113SN	

NO.1	
PART NO	vigor
2	130±30
3	160±30
4	260±30

NO.3	
PART NO	NOTE
1~9	SERIAL NUMBER

NO.2	
PART NO	MATERIAL/QTY.
S	SUS/1PC
D	SUS/2PCS

NO.4	
PART NO	NOTE
B	Bulk
R	Tape&Reel



Circuit diagram

⑥	Dust cover	2	Kapton film	Yellow
⑤	Terminal	4	Phosphor Bronze	Ag-PLATED
④	Shell	1	Sheet Iron	Natural
③	Contact	1	Stainless Steel	Ag-PLATED
②	Base	1	LCP	self-colored
①	Keystoke	1	NYLON	Black
ITEM	PART NAME	QTY.	MATERIAL	FINISHING

APPROVALS		DATE	DERION 德之盾 ELECTRONICS CO.,LTD									
DRAWN	G.M Chen	2011/3/18	TITLE:	TACT SWITCHES								
CHECKED			PART NO.	TD-1113SA-AXN-XXX								
APPROVALS			TOLERANCES ARE	<table border="1"> <tr> <td>30~以上</td> <td>±0.30</td> </tr> <tr> <td>10~30</td> <td>±0.20</td> </tr> <tr> <td>5~10</td> <td>±0.15</td> </tr> <tr> <td>~ 5</td> <td>±0.10</td> </tr> </table>	30~以上	±0.30	10~30	±0.20	5~10	±0.15	~ 5	±0.10
30~以上	±0.30											
10~30	±0.20											
5~10	±0.15											
~ 5	±0.10											
			ANGLE	UNIT: mm SCALE: 1:1 PROJ:								
			±2'	DRAWING NO.								

ECN NO.	REV.	DATE.	NEW	CHANGE.	CHECK.	APPRO.
	A					
			DESCRIPTION.			